



PrincetonWS™

PRINCETON™ 34-60W 1500MM WATTAGE SWITCHABLE LED LINEAR LIGHT MICROPRISMATIC 4000K

- Wattage Switchable Low Glare Surface Mount Commercial Linear as perfect energy saving solution to fluorescent fittings.
- Robust quality housing with micro-prismatic optics ensures even and uniform light distribution with minimal glare UGR19.
- Drop down gear tray can be locked after installation and maintenance for safer operation.
- Non dimmable driver with push-fit terminal enables rapid installation.
- Wattage Switchable during installation between 34W/43W/52W and 60W.

Code	Version	Colour	Watts	Lumens	lm/W	UGR	CRI
LN215001	Non-Dimmable	4000K	34 / 43 / 52 / 60W	4080-7200lm	Up to 120lm/W	19	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

PrincetonWS™

PRINCETON™ 34-60W 1500MM WATTAGE SWITCHABLE LED LINEAR LIGHT MICROPRISMATIC 4000K

Specifications and Benefits

Ingress Protection Rating	IP20
Operating Temperature Range	-15°C / +40°C
Mounting Type	Surface mounted
Certification	CE
Protection Class	Class I
Installation Location	Indoor
Body Material	Aluminium, PC
Cover Material	PC
Finishing	White
Available accessories	N/A

Photometric Specifications

Lumens	34W 4080lm
	43W 5160lm
	52W 6240lm
	60W 7200lm
Efficiency	Up to 120lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<3
Beam Angle	72°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Technical Specifications

Wattage	34 / 43 / 52 / 60W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>50,000
Lifetime Hours	L70 B50 50,000hrs L80 B20 50,000hrs
Energy Rating	E
Insulation Coverable	N/A
Inrush Current	29A

Logistic Details

EAN / Barcode	3609640148959
Product Weight	3200g
Product Dimensions (ODxH / LxWxH)	1505 x 180 x 85mm
Boxed Product Weight	3500g
Boxed Product Dimensions (LxWxH)	1530 x 183 x 90mm
Outer Carton Boxed Product Quantity	4 pcs
Outer Carton Dimensions (LxWxH)	1550 x 390 x 205mm

