



LouvreCWS

• DALI Driver for LouvreCWS

Code	Power	Dimming	Input Voltage & Frequency	Output Voltage	Output Current	Protection Class
DR158637	10 - 30W	DALI-2 / PUSH DIM	220 - 240 Vac / 180 - 264 Vdc 50/60Hz	9 - 42 VDC	400 - 750mA Maxi	SELV Class II





01/08/2025

Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.



LouvreCWS

DALI DRIVER

Features					
Input Voltage	220 - 240 Vac / 180 - 264 Vdc				
Output Voltage	9 - 42 VDC				
Output Current	400 - 750mA Maxi				
Power	10 - 30W				
Electrical Protection Class	SELV Class II				
Dimming	DALI-2 / PUSH DIM				
Ingress Protection Rating	IP20				
Operating Temperature	-20°C / 45°C				
Case Temperature	90°C				
Power Factor	>0.95				

Logistic	
EAN	3609640158637

01/08/2025