




Spheral

SPHERAL™ 18W IP65 LED BULKHEAD WHITE 4000K MICROWAVE SENSOR

- IP65 18W Bulkhead with opal polycarbonate IK10 diffuser for even and uniform light distribution offer best value for money.
- IP65 rated rear and side entry access wiring compartment enable quick and simple through-wiring and product installation.
- Microwave Sensor version with daylight harvesting feature, 110° detection range up to 4 meter and adjustable hold time configurations from 5 seconds to 30 minutes available.
- Suitable for ambient temperatures from -20°C to +45°C.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
BH150433	Microwave Sensor	4000K	18W	1800lm	100lm/W	80





Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.



Spheral^{*}


SPHERAL™ 18W IP65 LED BULKHEAD WHITE 4000K MICROWAVE SENSOR


Specifications and Benefits	
Ingress Protection Rating	IP65
IK Rating	IK10
Operating Temperature Range	-25°C / +45°C
Mounting Type	Surface mounted / Wall mounted
Certification	CE
Protection Class	Class II
Installation Location	Indoor / Outdoor
Body Material	Plastic
Cover Material	PC
Finishing	White
Available accessories	N/A

Colour Temperature 4000K Light Colour Definition Neutra SDCM <6 Beam Angle 120° CRI >80 Dimming Type Microw	
Colour Temperature 4000K Light Colour Definition Neutra SDCM <6 Beam Angle 120° CRI >80 Dimming Type Microw	
Light Colour Definition Neutral SDCM <6 Beam Angle 120° CRI >80 Dimming Type Microw	00lm/W
SDCM <6 Beam Angle 120° CRI >80 Dimming Type Microw	
Beam Angle 120° CRI >80 Dimming Type Microw	White
CRI >80 Dimming Type Microw	
Dimming Type Microw	
	ave Sensor
Distribution Direct	

Technical Specifications	
Wattage	18W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.8
Switching Cycles	>25,000
Lifetime Hours	L70 B50 50,000hrs L80 B20 50,000hrs
Energy Rating	D
Insulation Coverable	N/A
Inrush Current	10A

Logistic Details		
EAN / Barcode	3609640150433	
Product Weight	970g	
Product Dimensions (ODxH / LxWxH)	Ø330 x 78mm	
Boxed Product Weight	1060g	
Boxed Product Dimensions (LxWxH)	333 x 80 x 333mm	
Outer Carton Boxed Product Quantity	10 pcs	
Outer Carton Dimensions (LxWxH)	425 x 695 x 360mm	





10/30/2024