




## **Asimes**

## ASIMES™ 30W IP65 LED BULKHEAD WHITE 3CCT ASYMMETRICAL

- Colour Switchable IP65 Asymetrical Bulkhead with opal polycarbonate IK10 diffuser for even and uniform light distribution. Perfect for demanding wall and ceiling installations.
- 3 Colour Selections available for ultimate flexibility in every application.
- IP65 rated rear entry access wiring compartment enable quick and simple through-wiring and product installation.
- Suitable for ambient temperatures from -20°C to +45°C.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
BH156824	Non-Dimmable	3000 / 3500 / 4000K	30W	2300-2500lm	Up to 83lm/W	80





Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.



## **Asimes**


## ASIMES™ 30W IP65 LED BULKHEAD WHITE 3CCT ASYMMETRICAL


Specifications and Benefits				
Ingress Protection Rating	IP65			
IK Rating	IK10			
Operating Temperature Range	-25°C / +45°C			
Mounting Type	Surface mounted / Wall mounted			
Certification	CE			
Protection Class	Class II			
Installation Location	Indoor / Outdoor			
Body Material	Plastic			
Cover Material	PC			
Available accessories	N/A			

Photometric Specifications				
Lumens	2300 / 2500 / 2400lm			
Efficiency	Up to 83lm/W			
Colour Temperature	3000 / 3500 / 4000K			
Light Colour Definition	Switchable White			
SDCM	<6			
Beam Angle	120°			
CRI	>80			
Dimming Type	Non-Dimmable			
Distribution	Direct			

Technical Specifications				
Wattage	30W			
Nominal Voltage	220-240Vac			
Frequency	50/60Hz			
Power Factor	>0.5			
Switching Cycles	>100,000			
Lifetime Hours	L70 B50 50,000hrs L80 B50 50,000hrs			
Insulation Coverable	N/A			

Logistic Details				
EAN / Barcode	3609640156824			
Product Weight	820g			
Product Dimensions (ODxH / LxWxH)	Ø355 x 115mm			
Boxed Product Weight	1000g			
Boxed Product Dimensions (LxWxH)	357 x 357 x 117mm			
Outer Carton Boxed Product Quantity	10 pcs			
Outer Carton Dimensions (LxWxH)	375 x 735 x 605mm			





10/30/2024