



FaloCS™

FALOCS™ 5W ADJUSTABLE COLOUR SWITCHABLE DIMMABLE LED DOWNLIGHT 3CCT 2700/3000/4000K

- Colour Switchable IP44 Adjustable LED Downlight (120lm/W) with integrated Triac Dimmable LED driver. Coverable with any type of insulation material and airtight tested.
- Rapid tool-free installation through loop in/loop out push-fit wiring terminals with strain relief.
- Compact integrated low profile design with insulation cover allow for use in shallow voids up to 50mm.
- Colour Switchable between 2700/3000/4000K.
- LEDchroic lens design with 60° beam angle imitates the appearance of halogen lamps and provides controlled, uniform light distribution with minimal glare.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
DL149581	Dimmable	2700 / 3000 / 4000K	5W	446-496lm	Up to 120lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

FaloCS™

FALOCS™ 5W ADJUSTABLE COLOUR SWITCHABLE DIMMABLE LED DOWNLIGHT 3CCT 2700/3000/4000K

Specifications and Benefits

Ingress Protection Rating	IP44
Operating Temperature Range	-10°C / +35°C
Mounting Type	Recessed
Cutout Dimension	70mm
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	PC
Cover Material	PC
Finishing	White
Available accessories	N/A

Technical Specifications



Wattage	5W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.8
Switching Cycles	>100,000
Lifetime Hours	L70 B50 30,000hrs L80 B20 30,000hrs
Energy Rating	E
Insulation Coverable	YES
Inrush Current	5A

Photometric Specifications

Lumens	600 / 600 / 600lm
Useful Lumens	446 / 496 / 470lm
Efficiency	Up to 120lm/W
Colour Temperature	2700 / 3000 / 4000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	60°
CRI	>80
Dimming Type	Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640149581
Product Weight	122g
Product Dimensions (ODxH / LxWxH)	Ø86 x 61mm
Recess Depth	62mm
Boxed Product Weight	180g
Boxed Product Dimensions (LxWxH)	78 x 90 x 90mm
Outer Carton Boxed Product Quantity	48 pcs
Outer Carton Dimensions (LxWxH)	380 x 290 x 340mm



10/30/2024