



ONExBAFFLE™

ONExBAFFLE™ IP65 COLOUR & WATTAGE SELECTABLE BAFFLE LED DOWNLIGHT

- Colour & Wattage Switchable Baffled Triac dimmable LED Fire Rated LED Downlight.
- IP65 sleek baffled design to reduce glare. Supplied with White Aluminium Bezel. Black and Satin Nickel options available.
- Rapid tool-free installation through loop in / loop out push-fit wiring terminals with strain relief.
- Compact integrated design with insulation cover allow for use in shallow voids up to 73mm. Downlight and driver are insulation coverable.
- Tested in 30, 60 and 90 minutes fire-rated ceilings according to EN1365-2.

Code	Version	Colour	Watts	Lumens	lm/W	UGR	CRI
DL151379	Dimmable	2700 / 3000 / 4000K	3.5 / 5.5 / 7W	260-560lm	Up to 85lm/W	19	90



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

ONExBAFFLE™

ONExBAFFLE™ IP65 COLOUR & WATTAGE SELECTABLE BAFFLE LED DOWNLIGHT

Specifications and Benefits

Ingress Protection Rating	IP65
Operating Temperature Range	-20°C / +45°C
Mounting Type	Recessed
Positional Adjustment	Fixed
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Steel, PC
Cover Material	PC
Finishing	White
Available accessories	<ul style="list-style-type: none"> DL151348 - Alu Baffle Bezel Black DL151362 - Alu Baffle Bezel Satin Nickel

Technical Specifications

Wattage	3.5 / 5.5 / 7W
Nominal Voltage	220-240Vac
Frequency	50Hz
Power Factor	>0.9
Switching Cycles	>100,000
Lifetime Hours	L70 B50 50,000hrs L80 B20 50,000hrs
Insulation Coverable	YES
Inrush Current	40A

Photometric Specifications

Lumens	3.5W - 260 / 300 / 290lm 5.5W - 390 / 450 / 420lm 7W - 470 / 560 / 500lm
Efficiency	Up to 85lm/W
Colour Temperature	2700 / 3000 / 4000K
Light Colour Definition	Switchable White
SDCM	<4
Beam Angle	55°
CRI	>90
Dimming Type	Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640151379
Product Weight	0g
Product Dimensions (ODxH / LxWxH)	Ø88 x 75mm
Recess Depth	73mm
Boxed Product Weight	0g
Boxed Product Dimensions (LxWxH)	0 x 0 x 0mm
Outer Carton Boxed Product Quantity	0 pcs
Outer Carton Dimensions (LxWxH)	0 x 0 x 0mm

