



VelosCS™

VELOSCS™ 30W LED IP65 COLOUR SWITCHABLE ADJUSTABLE FLOODLIGHT BLACK 3000/3500/4000K

- Colour Switchable IP65 IK07 Residential LED Floodlight.
- Aluminium housing for excellent heat dissipation pre-wired with 800mm cable for ease of installation.
- Salt spray tested and approved, perfect solution for residential coastal applications.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
FL153823	Non-Dimmable	3000 / 3500 / 4000K	30W	3600-3750lm	Up to 120lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

VelosCS™

VELOSCS™ 30W LED IP65 COLOUR SWITCHABLE ADJUSTABLE FLOODLIGHT BLACK 3000/3500/4000K

Specifications and Benefits

Ingress Protection Rating	IP65
IK Rating	IK07
Operating Temperature Range	-20°C / +40°C
Mounting Type	Surface mounted / Wall mounted
Certification	CE
Protection Class	Class I
Installation Location	Indoor / Outdoor
Body Material	Aluminium
Cover Material	Glass
Finishing	Black
Available accessories	N/A

Technical Specifications



Wattage	30W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>20,000
Lifetime Hours	L70 B50 30,000hrs L80 B20 10,000hrs
Energy Rating	E
Insulation Coverable	NO
Inrush Current	0.75A

Photometric Specifications

Lumens	3600 / 3750 / 3600lm
Useful Lumens	3600 / 3750 / 3600lm
Efficiency	Up to 120lm/W
Colour Temperature	3000 / 3500 / 4000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	110°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Logistic Details

EAN / Barcode	3609640153823
Product Weight	890g
Product Dimensions (ODxH / LxWxH)	163 x 63 x 110mm
Boxed Product Weight	980g
Boxed Product Dimensions (LxWxH)	168 x 118 x 61mm
Outer Carton Boxed Product Quantity	30 pcs
Outer Carton Dimensions (LxWxH)	372 x 330 x 355mm



10/30/2024