



## **VelosCS**

## VELOSCS™ 10W LED IP65 COLOUR SWITCHABLE ADJUSTABLE FLOODLIGHT BLACK 3000/3500/4000K

- Colour Switchable IP65 IK07 Residential LED Floodlight.
- · Aluminium housing for excellent heat dissipation pre-wired with 800mm cable for ease of installation.
- · Salt spray tested and approved, perfect solution for residential costal applications.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
FL157418	Non-Dimmable	3000 / 3500 / 4000K	10W	1200-1250lm	Up to 120lm/W	80





Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.



## **VelosCS**\*


## VELOSCS™ 10W LED IP65 COLOUR SWITCHABLE ADJUSTABLE FLOODLIGHT BLACK 3000/3500/4000K


Specifications and Benefits				
Ingress Protection Rating	IP65			
IK Rating	IK07			
Operating Temperature Range	-20°C / +40°C			
Mounting Type	Surface mounted			
Certification	CE			
Protection Class	Class I			
Installation Location	Indoor / Outdoor			
Body Material	Aluminium			
Cover Material	Glass			
Finishing	Black			
Available accessories	N/A			

Photometric Specifications	
Lumens	1200 / 1250 / 1200lm
Useful Lumens	1200 / 1250 / 1200lm
Efficiency	Up to 120Im/W
Colour Temperature	3000 / 3500 / 4000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	110°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Technical Specifications					
Wattage	10W				
Nominal Voltage	220-240Vac				
Frequency	50/60Hz				
Power Factor	>0.9				
Switching Cycles	>20,000				
Lifetime Hours	L70 B50 30,000hrs L80 B20 10,000hrs				
Energy Rating	E				
Insulation Coverable	NO				
Inrush Current	0.25				

Logistic Details					
EAN / Barcode	3609640157418				
Product Weight	221g				
Product Dimensions (ODxH / LxWxH)	108 x 56 x 77mm				
Boxed Product Weight	260g				
Boxed Product Dimensions (LxWxH)	113 x 83 x 65mm				
Outer Carton Boxed Product Quantity	50 pcs				
Outer Carton Dimensions (LxWxH)	245 x 438 x 348mm				





10/30/2024