



VelosCS

VELOSCS™ 100W LED IP65 COLOUR SWITCHABLE ADJUSTABLE FLOODLIGHT BLACK 3000/3500/4000K

- Colour Switchable IP65 IK07 Residential LED Floodlight.
- · Aluminium housing for excellent heat dissipation pre-wired with 800mm cable for ease of installation.
- Salt spray tested and approved, perfect solution for residential costal applications.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
FL157425	Non-Dimmable	3000 / 3500 / 4000K	100W	12000-12500lm	Up to 115lm/W	80





Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.



VelosCS*


VELOSCS™ 100W LED IP65 COLOUR SWITCHABLE ADJUSTABLE FLOODLIGHT BLACK 3000/3500/4000K


Specifications and Benefits	
Ingress Protection Rating	IP65
IK Rating	IK07
Operating Temperature Range	-20°C / +40°C
Mounting Type	Surface mounted
Certification	CE
Protection Class	Class I
Installation Location	Indoor / Outdoor
Body Material	Aluminium
Cover Material	Glass
Finishing	Black
Available accessories	N/A

Photometric Specifications	
Lumens	12000 / 12500 / 12000lm
Useful Lumens	12000 / 12500 / 12000lm
Efficiency	Up to 115lm/W
Colour Temperature	3000 / 3500 / 4000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	110°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Technical Specifications	
Wattage	100W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Switching Cycles	>20,000
Lifetime Hours	L70 B50 30,000hrs L80 B20 10,000hrs
Energy Rating	Е
Insulation Coverable	NO
Inrush Current	2.5

Logistic Details	
EAN / Barcode	3609640157425
Product Weight	982g
Product Dimensions (ODxH / LxWxH)	282 x 65 x 190mm
Boxed Product Weight	1100g
Boxed Product Dimensions (LxWxH)	287 x 197 x 65mm
Outer Carton Boxed Product Quantity	10 pcs
Outer Carton Dimensions (LxWxH)	207 x 590 x 350mm





10/30/2024