



## ProximusWS™

### PROXIMUSWS™ IP66 IK08 WATTAGE SELECTABLE FLOODLIGHT 120/150/200W 4000K ASYMETRICAL

- Wattage Selectable High Power impact resistant IP66 LED Floodlight with picture superior efficiency of up to 160lm/W.
- Polycarbonate assymmetrical lense.
- Integrated non dimmable LED driver pre-wired with 1000mm AC cable for ease of installation.
- Suitable for -40°C - +50°C ambient working temperature.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
<b>FL157807</b>	Non-Dimmable	4000K	120 / 150 / 200W	19200-32000lm	Up to 160lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## ProximusWS™

### PROXIMUSWS™ IP66 IK08 WATTAGE SELECTABLE FLOODLIGHT 120/150/200W 4000K ASYMETRICAL

#### Specifications and Benefits

Ingress Protection Rating	IP66
IK Rating	IK08
Operating Temperature Range	-40°C / +50°C
Mounting Type	Surface mounted
Certification	CE
Protection Class	Class I
Installation Location	Indoor / Outdoor
Body Material	Aluminium
Cover Material	PC
Available accessories	N/A

#### Technical Specifications

Wattage	120 / 150 / 200W
Nominal Voltage	220-277Vac
Frequency	50/60Hz
Switching Cycles	>40,000
Lifetime Hours	L70 B50 100,000hrs L80 B20 50,000hrs
Energy Rating	B
Insulation Coverable	NO

#### Photometric Specifications

Lumens	120W 19200lm 150W 24000lm 200W 32000lm
Efficiency	Up to 160lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<6
Beam Angle	50 x 100°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

#### Logistic Details

EAN / Barcode	3609640157807
Product Weight	4200g
Product Dimensions (ODxH / LxWxH)	390 x 64 x 342mm
Boxed Product Weight	5200g
Boxed Product Dimensions (LxWxH)	0 x 0 x 0mm
Outer Carton Boxed Product Quantity	1 pcs
Outer Carton Dimensions (LxWxH)	110 x 375 x 440mm

