



ClearVu

CLEARVU™ GU10 5W 38° DIMMABLE LED LAMP 4000K

- Cost effective and super reliable GU10 lamp range with advanced thermal management to control key component temperatures.
- Single Colour version with LEDchroic lens design with 38° beam angle imitates the appearance of halogen lamps and provides controlled, uniform light distribution with minimal glare.
- Designed and tested for suitable use in enclosed fire rated and insulation coverable lighting fixtures. Excellent dimming compatibility with all market common dimmers in Europe.

Code	Version	Colour	Watts	Lumens	Useful lumens	lm/W	Beam	CRI
LA150570	Dimmable	4000K	5W	500lm	39lm	100lm/W	38°	80





Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.



Clear**V**u

CLEARVU™ GU10 5W 38° DIMMABLE LED LAMP 4000K

Specifications and Benefits	
Ingress Protection Rating	IP20
Operating Temperature Range	-10°C / +30°C
Mounting Type	N/A
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium, PC
Cover Material	PC
Finishing	White
Available accessories	N/A

Photometric Specifications	
Lumens	500lm
Useful Lumens	39lm
Efficiency	Up to 100lm/W
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<6
Beam Angle	38°
CRI	>80
Dimming Type	Dimmable
Distribution	Direct

Technical Specifications	
Wattage	5W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.7
Switching Cycles	>12,500
Lifetime Hours	L70 B50 15,000hrs L80 B20 15,000hrs
Energy Rating	F
Insulation Coverable	N/A
Inrush Current	2A

0150570
6mm
62mm
30 x 280mm



