



## Clear VuCS

## CLEARVU CS™ 5W GU10 NON-DIMMABLE LED LAMP 3CCT 2700/3000/4000K

- Cost effective and super reliable GU10 lamp range with advanced thermal management to control key component temperatures.
- Colour Selectable version with 3CCT Dip switch in 38° lense to select colour temperature before or even after installation between 2700K/3200K/4000K.
- Designed and tested for suitable use in enclosed fire rated and insulation coverable lighting fixtures. Excellent dimming compatibility with all market common dimmers in Europe.

Code	Version	Colour		Lumens	Useful lumens	lm/W		
	Non-Dimma-	2700 / 3200 /	6W	500-	400 / 470 /	Up to	38°	80





Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.



## Clear VuCS


## CLEARVU CS™ 5W GU10 NON-DIMMABLE LED LAMP 3CCT 2700/3000/4000K

Specifications and Benefits					
Ingress Protection Rating	IP20				
Operating Temperature Range	-20°C / +40°C				
Mounting Type	N/A				
Cutout Dimension	N/Amm				
Certification	CE				
Protection Class	Class II				
Installation Location	Indoor				
Body Material	Aluminium, PC				
Cover Material	PC				
Finishing	White				
Available accessories	N/A				

Photometric Specifications		
Lumens	500 / 580 / 550lm	
Useful Lumens	400 / 470 / 440lm	
Efficiency	Up to 96lm/W	
Colour Temperature	2700 / 3200 / 4000K	
Light Colour Definition	Switchable White	
SDCM	<6	
Beam Angle	38°	
CRI	>80	
Dimming Type	Non-Dimmable	
Distribution	Direct	

Technical Specifications				
Wattage	6W			
Nominal Voltage	220-240Vac			
Frequency	50/60Hz			
Power Factor	>0.5			
Switching Cycles	>12,500			
Lifetime Hours	L70 B50 25,000hrs L80 B20 15,000hrs			
Energy Rating	F			
Insulation Coverable	N/A			
Inrush Current	3A			

Logistic Details		
EAN / Barcode	3609640157937	
Product Weight	0g	
Product Dimensions (ODxH / LxWxH)	Ø50 x 55mm	
Boxed Product Weight	0g	
Boxed Product Dimensions (LxWxH)	132 x 267 x 108mm	
Outer Carton Boxed Product Quantity	1 pcs	
Outer Carton Dimensions (LxWxH)	170 x 595 x 290mm	



10/30/2024