



TrofferCWS™

TF6262CWS™ 622 X 622 25W/36W LED TROFFER PANEL NON DIMMABLE 2CCT 3000/400K

- Colour & Wattage Switchable high-efficiency (120lm/W) LED TrofferPanel uses edge-lit technology to replicate the appearance of traditional direct/indirect luminaires.
- Microprismatic diffuser (UGR<19) significantly reduces glare and enhances visual comfort which makes the Troffer Panel ideal for a wide range of commercial applications, including schools and offices.
- Flicker-free non-dimmable LED driver pre-wired for simplified and fast installation. 1.2m safety cable included.
- 2 Wattage and 2 Colour Selections available for ultimate flexibility in every application.

Code	Version	Colour	Watts	Lumens	lm/W	UGR	CRI
LP155803	Non-Dimmable	3000 / 4000 /K	25 / 36W	2740-4320lm	Up to 120lm/W	19	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

TrofferCWS™

TF6262CWS™ 622 X 622 25W/36W LED TROFFER PANEL NON DIMMABLE 2CCT 3000/400K

Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK02
Operating Temperature Range	-10°C / +40°C
Mounting Type	Recessed
Positional Adjustment	Fixed
Certification	CE
Protection Class	Class II
Installation Location	Indoor
Body Material	Aluminium
Cover Material	PC
Available accessories	<ul style="list-style-type: none"> • DR159429 - DALI driver • DR159481 - 1-10V driver

Technical Specifications

Wattage	25 / 36W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.9
Lifetime Hours	L70 B50 50,000hrs L80 B20 50,000hrs
Insulation Coverable	NO

Photometric Specifications

Lumens	25W - 2740 / 3000 / lm 36W - 3880 / 4320 / lm
Efficiency	Up to 120lm/W
Colour Temperature	3000 / 4000 /K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	90°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct / Indirect

Logistic Details

EAN / Barcode	3609640155803
Product Weight	1600g
Product Dimensions (ODxH / LxWxH)	622 x 622 x 49mm
Recess Depth	49mm
Boxed Product Weight	2600g
Boxed Product Dimensions (LxWxH)	50 x 630 x 675mm
Outer Carton Boxed Product Quantity	5 pcs
Outer Carton Dimensions (LxWxH)	695 x 305 x 745mm

