SWITCH LITE®
ENERGY SAVING SMART LIGHTING SOLUTIONS!

# Trac™

## TRAC™ GU10 ADJUSTABLE GLOBAL TRACK HEAD BLACK SHORT FORM

- Adjustable single circuit track spotlight and slimline track adaptor with GU10 6W Colour Selectable Lamp or for your choice GU10 lamps.
- Track lighting offers maximum flexibility for retail and commercial applications where light sources must be adaptable for changes in displays. Ready made track kit available for simple installation. Available in black and white.
- 350° Adjustable Rotation & 90° Tilt.
- For use with GU10 lamps up to max 35W.

| Code | CRI |
|---|---|
| **RT154219** | N/A |

Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

SWITCH LITE®
ENERGY SAVING SMART LIGHTING SOLUTIONS!

# Trac™

## TRAC™ GU10 ADJUSTABLE GLOBAL TRACK HEAD BLACK SHORT FORM

| Specifications and Benefits | |
|---|---|
| Ingress Protection Rating | IP20 |
| Operating Temperature Range | -10°C / +50°C |
| Certification | CE |
| Protection Class | Class I |
| Installation Location | Indoor |
| Body Material | Aluminium |
| Cover Material | Glass |
| Finishing | Black |
| Available accessories | N/A |

| Photometric Specifications | |
|---|---|
| Colour Temperature | N/AK |
| SDCM | <N/A |
| Beam Angle | N/A° |
| CRI | >N/A |
| Distribution | Direct |

| Technical Specifications | |
|---|---|
| Nominal Voltage | 220-240Vac |
| Frequency | 0Hz |
| Power Factor | >0 |
| Switching Cycles | >0 |
| Lifetime Hours | L70 B50 N/Ahrs<br>L80 0hrs |
| Insulation Coverable | N/A |

| Logistic Details | |
|---|---|
| EAN / Barcode | 3609640154219 |
| Product Weight | 217g |
| Product Dimensions (ODxH / LxWxH) | Ø53 x 100mm |
| Boxed Product Weight | 328g |
| Boxed Product Dimensions (LxWxH) | 180 x 70 x 70mm |
| Outer Carton Boxed Product Quantity | 50 pcs |
| Outer Carton Dimensions (LxWxH) | 385 x 375 x 375mm |






10/30/2024