



BeamVario CS™

BEAMVARIO CS™ 23W MULTI BEAM 24°/38°/60° SINGLECIRCUIT COLOUR SWITCHABLE TRACK 3000K/3500K/4000K WHI

- Colour Selectable single circuit track LED Spotlight with adjustable beam angle for maximal flexibility in retail environments.
- Colour Switch located on back-site of Trackhead for simple adjustment of colour temperature between 2700K, 3200K and 4000K even after initial installation.
- Beam angle adjustment and focusing through rotating front-cap between 60°, 38° and 24°. Different dial scale stand for individual aperture.
- 330° horizontal and 90° vertical adjustment to adapt to changing points of sales environments in stores.

| Code | Version | Colour | Watts | Lumens | lm/W | CRI |
|-----------------|--------------|---------------------|-------|-------------|---------------|-----|
| RT158415 | Non-Dimmable | 2700 / 3200 / 4000K | 23W | 2300-2600lm | Up to 113lm/W | 80 |



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

BeamVario CS™

BEAMVARIO CS™ 23W MULTI BEAM 24°/38°/60° SINGLECIRCUIT COLOUR SWITCHABLE TRACK 3000K/3500K/4000K WHI

Specifications and Benefits

| | |
|-----------------------------|---------------|
| Ingress Protection Rating | IP20 |
| IK Rating | IK06 |
| Operating Temperature Range | -20°C / +40°C |
| Certification | CE |
| Protection Class | Class I |
| Installation Location | Indoor |
| Body Material | Aluminium, PC |
| Cover Material | PC |
| Finishing | White |
| Available accessories | N/A |

Technical Specifications



| | |
|----------------------|--|
| Wattage | 23W |
| Nominal Voltage | 220-240Vac |
| Frequency | 50/60Hz |
| Power Factor | >0.8 |
| Switching Cycles | >15,000 |
| Lifetime Hours | L70 B50 25,000hrs L80 B20 15,000hrs |
| Energy Rating | E |
| Insulation Coverable | N/A |
| Inrush Current | 5A |

Photometric Specifications

| | |
|-------------------------|----------------------|
| Lumens | 2300 / 2600 / 2500lm |
| Useful Lumens | 2200 / 2500 / 2400lm |
| Efficiency | Up to 113lm/W |
| Colour Temperature | 2700 / 3200 / 4000K |
| Light Colour Definition | Switchable White |
| SDCM | <6 |
| Beam Angle | 24/38/60° |
| CRI | >80 |
| Dimming Type | Non-Dimmable |
| Distribution | Direct |

Logistic Details

| | |
|-------------------------------------|-------------------|
| EAN / Barcode | 3609640158415 |
| Product Weight | 0g |
| Product Dimensions (ODxH / LxWxH) | Ø84 x 140mm |
| Boxed Product Weight | 0g |
| Boxed Product Dimensions (LxWxH) | 215 x 87 x 110mm |
| Outer Carton Boxed Product Quantity | 20 pcs |
| Outer Carton Dimensions (LxWxH) | 250 x 465 x 470mm |



10/30/2024