



## BeamVario CS™

### BEAMVARIO CS™ 23W MULTI BEAM 24°/38°/60° SINGL CIRCUIT COLOUR SWITCHABLE TRACK 2700K/3200K/4000K BLA

- Colour Selectable single circuit track LED Spotlight with adjustable beam angle for maximal flexibility in retail environments.
- Colour Switch located on back-site of Trackhead for simple adjustment of colour temperature between 2700K, 3200K and 4000K even after initial installation.
- Beam angle adjustment and focusing through rotating front-cap between 60°, 38° and 24°. Different dial scale stand for individual aperture.
- 330° horizontal and 90° vertical adjustment to adapt to changing points of sales environments in stores.

Code	Version	Colour	Watts	Lumens	lm/W	CRI
<b>RT158422</b>	Non-Dimmable	2700 / 3200 / 4000K	23W	2000-2300lm	Up to 100lm/W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## BeamVario CS™

### BEAMVARIO CS™ 23W MULTI BEAM 24°/38°/60° SINGL CIRCUIT COLOUR SWITCHABLE TRACK 2700K/3200K/4000K BLA

#### Specifications and Benefits

Ingress Protection Rating	IP20
IK Rating	IK06
Operating Temperature Range	-20°C / +40°C
Certification	CE
Protection Class	Class I
Installation Location	Indoor
Body Material	Aluminium, PC
Cover Material	PC
Finishing	Black
Available accessories	N/A

#### Technical Specifications



Wattage	23W
Nominal Voltage	220-240Vac
Frequency	50/60Hz
Power Factor	>0.8
Switching Cycles	>15,000
Lifetime Hours	L70 B50 25,000hrs L80 B20 15,000hrs
Energy Rating	E
Insulation Coverable	N/A
Inrush Current	5A

#### Photometric Specifications

Lumens	2000 / 2300 / 2200lm
Useful Lumens	1920 / 2200 / 2100lm
Efficiency	Up to 100lm/W
Colour Temperature	2700 / 3200 / 4000K
Light Colour Definition	Switchable White
SDCM	<6
Beam Angle	N/A°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

#### Logistic Details

EAN / Barcode	3609640158422
Product Weight	0g
Product Dimensions (ODxH / LxWxH)	Ø84 x 140mm
Boxed Product Weight	0g
Boxed Product Dimensions (LxWxH)	215 x 87 x 110mm
Outer Carton Boxed Product Quantity	20 pcs
Outer Carton Dimensions (LxWxH)	250 x 465 x 470mm



10/30/2024