



CosmosProWS™

COSMOSPROWS™ 80/120/150W IP65 0-10V DIMMABLE Highbay 4000K

- Wattage Selectable High Power IK10 impact resistant IP65 LED Highbay with superior efficiency of up to 185lm/W.
- Tool free interchangeable Lense design. Comes with 110° lense as standard, 90° lense options available as accessory.
- Integrated 0-10V dimmable LED driver pre-wired with 1500mm cable/220mm dim wire for ease of installation. 800mm safety cable included.
- Zhaga base for plug and play Microwave or PIR Sensor Module with detection range up to 12m. Sensor options available as accessory.
- Suitable for -40° - +50° ambient working temperature.

Code	Version	Colour	Watts	CRI
HB157685	Non-Dimmable	4000K	80 / 120 / 150W	80



Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

CosmosProWS™

COSMOSPROWS™ 80/120/150W IP65 0-10V DIMMABLE HIGHBAY 4000K

Specifications and Benefits

Ingress Protection Rating	IP65
IK Rating	IK10
Operating Temperature Range	-40°C / +50°C
Positional Adjustment	Fixed
Certification	CE
Protection Class	Class I
Installation Location	Indoor
Body Material	Aluminium
Cover Material	PC
Available accessories	<ul style="list-style-type: none"> • HB159917 - Mounting Bracket • HB159177 - Alu Reflector • HB159184 - PC Reflector • HB158705 - Microwave Sensor • HB154547 - MS Remote Controller • HB159146 - PIR Sensor

Photometric Specifications

Lumens	80W 15000lm
	120W 22000lm
	150W 27000lm
Colour Temperature	4000K
Light Colour Definition	Neutral White
SDCM	<6
Beam Angle	110°
CRI	>80
Dimming Type	Non-Dimmable
Distribution	Direct

Technical Specifications

Wattage	80 / 120 / 150W
Nominal Voltage	220-Vac
Power Factor	>0.95
Lifetime Hours	L70 B50 hrs
Energy Rating	A
Insulation Coverable	N/A

Logistic Details

EAN / Barcode	3609640157685
Product Weight	1900g
Product Dimensions (ODxH / LxWxH)	Ø275 x 114mm
Boxed Product Weight	2700g
Boxed Product Dimensions (LxWxH)	0 x 0 x 0mm
Outer Carton Boxed Product Quantity	1 pcs
Outer Carton Dimensions (LxWxH)	185 x 320 x 320mm

